Technical datasheet

Agrolys WH100 L25

Agrotextiles - PP Woven groundcovers



Functions

Stimulates the growth of the plants which need a high reflection of light Improves coloration

Maintains soil health

Product Specifications

PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE				
		WARP	WEFT						
MATERIAL		PP	PP						
TISSUE COLOUR		white							
PATTERN		line 25 cm							
COLOUR LINING		blue							
TISSUE WEIGHT	ISO 3801	100		g/m²	± 5 %				
WIDTH		330 - 415 - 515		cm	± 2 cm				
LENGTH		100		m	± 2 %				

Technical characteristics

Technical characteristics							
PROPERTIES	TEST METHOD	VALUE		UNIT	TOLERANCE		
		WARP	WEFT				
BREAK ELONGATION	ISO 13934-1	18	17	%	± 20 %		
TENSILE STRENGTH	ISO 13934-1	850	700	N/5cm	± 20 %		
PERFORATION RESISTANCE	EN ISO 13433	18		mm	MAX		
UV-STABILIZATION	ISO 4892-3 cycle 3	800		kLy			
LIGHT REFLECTION		75		%			
SHRINKAGE	15' à 70 °C	1,5	1,0	%	± 20 %		
WATERPERMEABILITY	ISO 11058	0,010		m/s	± 50 %		
REMARKS	UV-Stabilization: Based on QUV testing min 7400 h (cycles of 5 h light exposure UV-A 340 nm 0,83 W/m² at 50°C and 1 h water spray), which corresponds theoretically to a solar irradiation of 800 kLY. In a climate zone of 90 kLy/y (Western Europe) this corresponds to 8-9 years. Max flash point $PP \pm 260$ °C Ignition temp $PP > 300$ °C						

This information contained in this document is based on testing carried out by our laboratory or external research institutes and literature data, and based on Mean Values. This TDS is valid until further notice. To the best of our knowledge and at the time of publication, this information is true and accurate. It shall however, in no event be held to constitute or imply warranty undertaking express or implied commitment from the part of BTT. No liability whatever can be accepted by BTT with regard to the handling, processing or use of the product concerned which must in all cases be used in accordance with all applicable laws and regulations. The mentioned characteristics are not valid when the fabric has been in contact with sulphur-, chlorine-, iron- and brominederivates, as well as with copper sulphates and if the product is not installed and used in strict accordance with the installation instructions.

Technical Datasheet 730: version 3 Date: 10/06/2025